



Editing date: November 2011

Edition: 01.

Revision date: November 2014

Revision: 01.

SP 300

Spray cleaner for silicone insulators and electric contacts

DESCRIPTION

SP300 is a deoxidant and degreasing spray specifically formulated to clean the silicone insulators of circuit breakers.

SP300 proved extremely effective to remove oxides, dirt, grease residues and carbon deposits.

Notwithstanding its strong dissolving action, the product gives no damage to elastomers, plastics, rubbers and painted surfaces.

SP300 can be also an effective cleaning and deoxidizing solution for electric contacts without jeopardizing the power transmission (e.g. sliding contacts, copper contacts, silver-plated and gold-plated contacts, graphite).

Don't use **SP300** on live electric or electronic devices. Be sure the product has completely evaporated before connecting the power supply again.

APPLICATIONS

SP300 reaches every equipment part to be cleaned easily. Evaporates quickly without leaving residues.

SP300 can be also a proper and fast cleaning solution for:

- ✓ electronic cards (also for the after-welding cleaning)
- ✓ electric components
- ✓ potentiometers
- ✓ contactors
- ✓ analytic and precision equipment
- ✓ electronic components

TYPICAL DATA

Appearance	spray liquid
Colour	colourless
Odour	Alcoholic
Specific gravity @ 15 °C	0,781
Flash point	< 62 °C
Dielectric strength	< 15 kV/mm

SAFETY

- No content of aromatic solvents, chlorinated solvents and benzene
- No content of halogenated hydrocarbons
- No CFC or other propellants alleged to damage ozone
- No residues and fast evaporation

HANDLING AND STORAGE

The product must be stored in a safe place protected against fire. For further information please refer to the safety data sheet. Spray cans are pressurised and must be kept in a safe place, away from heat, sparks, flames and any potential ignition source. Do not spray onto naked flames or any other incandescent or heated material. Disconnect tension before use. Do not spray on live electric and electronic devices including contacts and batteries. Use in a well aired place. Do not smoke while using the product and anywhere the product is used or stored. Spray carefully avoiding any contact of the product or its vapors with flames or uncovered electric devices.

USE GUIDELINES

Shake the spray can before use briefly. Avoid a prolonged spraying.

PACKAGING

SP300 is distributed as 400ml spray cans in 12 pcs carton.

Note

The data contained herein are given for information only. BB Technical Service cannot assume responsibility for the results obtained by others which methods are not under BB Technical Service control. It is user's responsibility to determine suitability for the user's purpose of any product mentioned herein. BB Technical Service disclaim all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of BB Technical Service products. BB Technical Service specifically disclaim any liability for consequential or incidental damages of any kind, including lost profits.



BB Technical Service S.R.L.

Company Registered Office: Via Torino 5 – 20814 Varedo (MB) – ITALY

Tel. +39 (0) 362 576038

website: www.bbtechnicalservice.it - e-mail: info@bbtechnicalservice.it

Quality Management System
UNI EN ISO 9001:2015
approved by RINA