

Edition date: Marzo 2013 Edition: 01.

Revision: - Revision:

SW 305

Spray cleaner for adhesion pre-treatment

DESCRIPTION

SW305 is a spray detergent recommended by Faiveley Transport for the right surfaces cleaning as adhesion pretreatment. Its formulation includes only non-CFC solvents.

The product is the also effective to remove any dirt and residue from metal parts.

USE GUIDELINES

Spray a proper quantity and wait for the full product evaporation until the surface will appear completely dry.

Due to its solvent based formulation, the product may damage some plastic materials and some paints and coatings. Perform careful preliminary tests when the product must be used in presence of sensitive materials. For further information, please contact BB Technical Service.

HANDLING AND STORAGE

SW305 is a flammable product. Store between +5°C and +25°C in a cool, well aired and dry place. In proper storage conditions the product keeps unchanged its properties.

Spray cans are pressurised and must be kept in a safe place, away from heat, sparks, flames and any potential ignition source. Do not spray onto naked flames or any other incandescent or heated material. Do not spray on live electric and electronic devices including contacts and batteries. Use in a well aired place. Do not smoke using the product and anywhere the product is used or stored. Spray carefully avoiding any contact of the product or its vapors with flames or uncovered electric devices. For further information, please refer to the safety data sheet.

TYPICAL PROPERTIES

Appearance	Flowing liquid
Colour	transparent
Odour	Mild
Solubility in water at 25 °C	Insoluble
Density at 25 °C (DIN 51757)	0,70 g/ml
TLV, ppm	346
Drying time at 25 °C (seconds)	60

PACKAGING

SW305 is supplied in 400 ml spray cans packaged in 12 pcs carton.

Note

The data contained herein are given for information only. BB Technical Service cannot assume responsibility for the results obtained by others whose methods are not under BB Technical Service control. It is user's responsibility to determine the suitability for the user's purpose of any product mentioned herein. BB Technical Service disclaim all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of BB Technical Service products. BB Technical Service specifically disclaim any liability for consequential or incidental damages of any kind, including lost profits.

