



Editing date: March 2012

Edition #: 01.

Revision date: September 2015

Revision #: 02

SW 435

Neutral pH water-based degreaser

DESCRIPTION

SW435 is a neutral pH cleaner developed to Faiveley Transport specifications for the preliminary cleaning of railway compressor and braking system components prior to maintenance operations.

SW 435 provides fast and effective cleaning. Its highly penetrating action and strong soil breaking capability make it effective even on carbonized grease deposits.

APPLICATIONS

SW435 is ideal for the external cleaning of radiators and screw units during routine, scheduled and predictive maintenance operations.

SW435 thoroughly degreases treated surfaces, preparing them for inspection for possible lubricant leakage using the specific **SW 354** detection spray.

The product requires no rinsing and does not damage metals or painted surfaces. The thin surfactant film left on the surfaces after cleaning helps prevent the adhesion of dirt and contaminants.

COMPATIBILITY

SW435 is safe for every kind of metals. It doesn't damage or blacken materials such as aluminium, copper, magnesium and their alloys.

HANDLING AND STORAGE

SW435 is safe for operators. Its formulation doesn't include caustic alkali or strongly aggressive substances.

DIRECTION OF USE

Use at low concentration (typical ranging: 1-10%). It does not exhaust its cleaning properties after few cleaning cycles.

Manual cleaning:

- ✓ Use a manual nebulizer
- ✓ Concentration of 8-10% in warm water is recommended for this application
- ✓ Let the product act for a few minutes

When cleaning the radiators, to obtain a proper result also on the honeycomb structures, start the compressor and spray the product solution directly on the radiator while the compressor is in action.

Perfect for washing in the ultrasound tanks, **SW435** is effective also to dissolve the greasy carbon deposits inside the oil separators restoring their performance promptly.

If used in jet tanks, we recommend working at 70°C to avoid foaming.

Its high penetrating action is effective either in warm or in cold treatment.

It is perfect also for use in the closed-tankbks washing machines. Easy to dose, it quickly dissolves in water without deposits.

PACKAGING

SW435 is available in 5 kg and 10 kg cans

Note

The data contained herein are given for information only. BB Technical Service cannot assume responsibility for the results obtained by others whose methods are not under BB Technical Service control. It is user's responsibility to determine suitability for the user's purpose of any product mentioned herein. BB Technical Service disclaim all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of BB Technical Service products. BB Technical Service specifically disclaim any liability for consequential or incidental damages of any kind, including lost profits.



BB Technical Service S.R.L.

Via Torino, 5 - 20814 Varedo (MB) - ITALY - Tel. +39 0362 576038
website: www.bbtechnicalservice.com - e-mail : info@bbtechnicalservice.it

Quality Management System
UNI EN ISO 9001-2015
approved by RINA